

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Product name	: Biogel
Product code	: D38
Type of product	: Detergent
Product group	: Cleaning product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category	: Professional use
Use of the substance/mixture	: See product bulletin for detailed information

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

CID LINES NV
Waterpoortstraat, 2
B-8900 Ieper - Belgique
T + 32 57 21 78 77 - F +32 57 21 78 79
sds@cidlines.com - <http://www.cidlines.com>

Importer

Best Veterinary Solutions, Inc
1716 Detroit St
P.O. Box 370
IA 50075 Ellsworth - United States of America
T 888-378-4045
<https://www.bestvetsolutions.com/>

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Australia	Poisons Information Centre		13 11 26	
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn B -1120 Brussels	+32 70 245 245	
Canada	CANUTEC Country Organization/Company Address Emergency number Comment		(613) 996-6666	
Finland	Poison Information Centre	P.O.B 790 (Tukholmankatu 17) HUS SF - 00029 Helsinki	+358 9 471 977	
Iceland	Eitrunarmiðstöð Landspítali	Fossvogi 108 Reykjavik	+354 543 22 22	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital MSD Msida	112	
Netherlands	Nationaal Vergiftigingen Informatie Centrum Uitsluitend bestemd om artsen te informeren bij accidentele vergiftigingen	Huispostnummer B.00.118, PO Box 85500 3508 GA Utrecht	+31 30 274 88 88	
New Zealand	The National Poisons Centre	University of Otago, 2nd Floor, Adams Building, 18 Frederick Street, 9016 Dunedin	0800 764 766 0800 POISON	
Switzerland	Centre Suisse d'Information Toxicologique Swiss Toxicological Information Centre, Schweizerisches Toxicologisches Informationszentrum STIZ	Freiestrasse 16 Postfach CH-8032 Zurich	+41 44 251 51 51 (International) 145 (National)	

Biogel

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	
USA	American Association of Poison Control Centers		1-800-222-1222	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Labelling according to OSHA 29 CFR 1910.1200

Skin Corr. 1A	H314
Eye Dam. 1	H318
Aquatic Chronic 3	H412

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

Serious eye damage/irritation. Skin corrosion/irritation.

2.2. Label elements

Labelling according to OSHA 29 CFR 1910.1200

Hazard pictograms (CLP)



GHS05

Signal word (CLP)	: Danger
Hazardous ingredients	: sodium hydroxide; caustic soda
Hazard statements (CLP)	: H314 - Causes severe skin burns and eye damage. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P260 - Do not breathe dust, mist, spray. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor/physician. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43	15 – 30	Flam. Liq. 2, H225
sodium hydroxide; caustic soda	(CAS-No.) 1310-73-2 (EC-No.) 215-185-5 (EC Index-No.) 011-002-00-6 (REACH-no) 01-2119457892-27	5 – 15	Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318

Biogel

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides,	(CAS-No.) 308062-28-4 (EC-No.) 931-292-6 (REACH-no) 01-2119490061-47	5 – 15	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
---	--	--------	--

Specific concentration limits:

Name	Product identifier	Specific concentration limits
sodium hydroxide; caustic soda	(CAS-No.) 1310-73-2 (EC-No.) 215-185-5 (EC Index-No.) 011-002-00-6 (REACH-no) 01-2119457892-27	(0.5 ≤C < 2) Skin Irrit. 2, H315 (0.5 ≤C < 2) Eye Irrit. 2, H319 (2 ≤C < 5) Skin Corr. 1B, H314 (5 ≤C < 100) Skin Corr. 1A, H314

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Seek medical attention immediately.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Seek medical advice (show the label where possible).
First-aid measures after eye contact	: Rinse immediately with plenty of water. Seek medical attention immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting because of corrosive effects. Take to hospital.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation of vapour can cause breathing difficulties. Cough. Sore throat.
Symptoms/effects after skin contact	: Redness, pain. Causes severe skin burns and eye damage.
Symptoms/effects after eye contact	: Redness, pain. Blurred vision. Tears. Serious damage to eyes.
Symptoms/effects after ingestion	: Burning sensation. Cough. Cramps. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Not flammable.
Explosion hazard	: Not expected to be a fire/explosion hazard under normal conditions of use.
Reactivity in case of fire	: At high temperature may liberate dangerous gases.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire	: Wear fire/flare resistant/retardant clothing. Eliminate all ignition sources if safe to do so.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Exercise caution when fighting any chemical fire. Do not enter fire area without proper protective equipment, including respiratory protection. Wear fire/flare resistant/retardant clothing. Heat resistant gloves.
Other information	: On exposure to high temperature, may decompose, releasing toxic gases.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection. Stop leak if safe to do so. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.1.1. For non-emergency personnel

Protective equipment	: Avoid all unnecessary exposure. Wear suitable protective clothing. Ensure adequate ventilation. Do not breathe vapours.
Emergency procedures	: Do not touch or walk on the spilled product. Evacuate area. Do not breathe vapours. Avoid contact with skin, eyes and clothing.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

Biogel

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Emergency procedures : Do not touch spilled material. Evacuate unnecessary personnel. Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak without risks if possible. Collect spillage. Use suitable disposal containers.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : When handling product, avoid contact with skin and eyes. Wear personal protective equipment. Do not breathe vapour/aerosol. Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool well ventilated place. Do not store in corrodable metal. Keep container closed when not in use. Protect from freezing.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethanol (64-17-5)		
Belgium	Local name	Alcool éthylique # Ethanol
Belgium	OEL TWA	1907 mg/m ³
Belgium	OEL TWA [ppm]	1000 ppm
Belgium	Regulatory reference	Koninklijk besluit/Arrêté royal 02/09/2018
Czech Republic	PEL (OEL TWA)	1000 mg/m ³
Czech Republic	PEL (OEL TWA) [ppm]	532 ppm
Czech Republic	NPK-P (OEL C)	3000 mg/m ³
Czech Republic	NPK-P (OEL C) [ppm]	1596 ppm
Germany	Local name	Ethanol
Germany	AGW (OEL TWA) [1]	380 mg/m ³
Germany	AGW (OEL TWA) [2]	200 ppm
Germany	Peak exposure limitation factor	2(II)
Germany	Remark	DFG;Y
Germany	Regulatory reference	TRGS900
Germany	Notes	
Netherlands	MAC-TGG (OEL TWA)	260 mg/m ³
Netherlands	MAC-TGG (OEL TWA) [ppm]	128 ppm
Netherlands	MAC-15 (OEL STEL)	1900 mg/m ³
Netherlands	MAC-15 (OEL STEL) [ppm]	986 ppm
United Kingdom	Local name	Ethanol
United Kingdom	WEL TWA (OEL TWA) [1]	1920 mg/m ³
United Kingdom	WEL TWA (OEL TWA) [2]	1000 ppm
United Kingdom	Regulatory reference	EH40/2005 (Third edition, 2018). HSE
Switzerland	MAK (OEL TWA) [1]	960 mg/m ³
Switzerland	MAK (OEL TWA) [2]	500 ppm
Switzerland	KZGW (OEL STEL)	1920 mg/m ³

Biogel

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Ethanol (64-17-5)		
Switzerland	KZGW (OEL STEL) [ppm]	1000 ppm

sodium hydroxide; caustic soda (1310-73-2)

DNEL/DMEL (Workers)

Long-term - local effects, inhalation 1 mg/m³

DNEL/DMEL (General population)

Long-term - local effects, inhalation 1 mg/m³

Ethanol (64-17-5)

DNEL/DMEL (Workers)

Acute - local effects, inhalation 1900 mg/m³

Long-term - systemic effects, dermal 343 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 950 mg/m³

DNEL/DMEL (General population)

Acute - local effects, inhalation 950 mg/m³

Long-term - systemic effects, oral 87 mg/kg bodyweight/day

Long-term - systemic effects, inhalation 114 mg/m³

Long-term - systemic effects, dermal 206 mg/kg bodyweight/day

PNEC (Water)

PNEC aqua (freshwater) 0.96 mg/l

PNEC aqua (marine water) 0.79 mg/l

PNEC aqua (intermittent, freshwater) 2.75 mg/l

PNEC (Sediment)

PNEC sediment (freshwater) 3.6 mg/kg dwt

PNEC sediment (marine water) 2.9 mg/kg dwt

PNEC (Soil)

PNEC soil 0.63 mg/kg dwt

PNEC (Oral)

PNEC oral (secondary poisoning) 0.72 g/kg food

PNEC (STP)

PNEC sewage treatment plant 580 mg/l

8.2. Exposure controls

Hand protection:

Wear suitable gloves resistant to chemical penetration

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Polyvinylchloride (PVC)	6 (> 480 minutes)	0.5	2 (< 1.5)	EN ISO 374

Eye protection:

Wear security glasses which protect from splashes

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear, Plastic	EN 166

Skin and body protection:

Wear suitable protective clothing

Type	Standard
	EN14605:2005+A1:2009

Biogel

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Respiratory protection:

Appropriate dust or mist respirator should be used if airborne particles are generated when handling this material

Device	Filter type	Condition	Standard
Disposable half mask	Filter E/P	Protection for Liquid particles, Vapour protection, Long term exposure	EN 132, EN 140

Personal protective equipment symbol(s):



Other information:

When using do not eat, drink or smoke. Provide local exhaust or general room ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: clear. amber.
Odour	: odourless.
Odour threshold	: No data available
pH	: ≈ 12 (1%)
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 50.5 °C Does not sustain combustion per ASTM D4206
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: ≈ 1.06 kg/l
Solubility	: Water: 100 %
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 800 – 2000 cP (10%)
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

Additional information	: No hazardous good class 3 according UN Manual of Tests and Criteria, part III, section 32.2.5 (combustibility is not sustained).
------------------------	--

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal conditions.

10.2. Chemical stability

Stable in use and storage conditions as recommended in item 7.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Aluminium. Strong acids.

10.6. Hazardous decomposition products

According to process conditions, hazardous decomposition products may be generated.

Biogel

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Ethanol (64-17-5)

LD50 oral rat	15010 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 14450 - 15560
LD50 oral	8300 mg/kg bodyweight Animal: mouse

Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides, (308062-28-4)

LD50 oral	1064 mg/kg
Skin corrosion/irritation	: Causes severe skin burns. pH: ≈ 12 (1%)
Serious eye damage/irritation	: Causes serious eye damage. pH: ≈ 12 (1%)
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

Biogel

LOAEL (oral, rat)	> 2000 mg/kg bodyweight
-------------------	-------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

Ethanol (64-17-5)

NOAEL (subchronic, oral, animal/male, 90 days)	< 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)

Aspiration hazard	: Not classified
-------------------	------------------

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

sodium hydroxide; caustic soda (1310-73-2)

EC50 - Crustacea [1]	40.4 mg/l Test organisms (species): Ceriodaphnia sp.
----------------------	--

Ethanol (64-17-5)

LC50 - Fish [1]	14.2 g/l Test organisms (species): Pimephales promelas
NOEC (chronic)	9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'

12.2. Persistence and degradability

Biogel

Persistence and degradability	The surfactant contained in this preparation complies with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.
-------------------------------	---

12.3. Bioaccumulative potential

Ethanol (64-17-5)

Partition coefficient n-octanol/water (Log Kow)	-0.35
---	-------

Biogel

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Amines, C12-14 (even numbered)-alkyldimethyl, N-oxides, (308062-28-4)

Partition coefficient n-octanol/water (Log Kow) 2.7

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Dispose in a safe manner in accordance with local/national regulations.
Waste treatment methods	: Dispose of this material and its container at hazardous or special waste collection point. Hazardous waste due to toxicity. Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: When totally empty, containers are recyclable like any other packing. Dispose in a safe manner in accordance with local/national regulations. Avoid release to the environment.
European List of Waste (LoW) code	: 07 06 01* - aqueous washing liquids and mother liquors
Switzerland - Waste code (VeVA)	: 07 06 01 - [ak] Aqueous washing liquids and aqueous mother liquors

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number

UN-No. (ADR)	: UN 1824
UN-No. (IMDG)	: UN 1824
UN-No. (IATA)	: UN 1824
UN-No. (ADN)	: UN 1824
UN-No. (RID)	: UN 1824

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: SODIUM HYDROXIDE SOLUTION
Proper Shipping Name (IMDG)	: SODIUM HYDROXIDE SOLUTION
Proper Shipping Name (IATA)	: Sodium hydroxide solution
Proper Shipping Name (ADN)	: SODIUM HYDROXIDE SOLUTION
Proper Shipping Name (RID)	: SODIUM HYDROXIDE SOLUTION
Transport document description (ADR)	: UN 1824 SODIUM HYDROXIDE SOLUTION, 8, II, (E)
Transport document description (IMDG)	: UN 1824 SODIUM HYDROXIDE SOLUTION, 8, II
Transport document description (IATA)	: UN 1824 Sodium hydroxide solution, 8, II
Transport document description (ADN)	: UN 1824 SODIUM HYDROXIDE SOLUTION, 8, II
Transport document description (RID)	: UN 1824 SODIUM HYDROXIDE SOLUTION, 8, II

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 8
Danger labels (ADR)	: 8



IMDG

Transport hazard class(es) (IMDG)	: 8
Danger labels (IMDG)	: 8



Biogel

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

IATA

Transport hazard class(es) (IATA) : 8

Danger labels (IATA) : 8



ADN

Transport hazard class(es) (ADN) : 8

Danger labels (ADN) : 8



RID

Transport hazard class(es) (RID) : 8

Danger labels (RID) : 8



14.4. Packing group

Packing group (ADR) : II

Packing group (IMDG) : II

Packing group (IATA) : II

Packing group (ADN) : II

Packing group (RID) : II

14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : Clean up even minor leaks or spills, if possible, without unnecessary risk

14.6. Special precautions for user

Special transport precautions : Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency, No naked flames, sparks, and do not smoke, Keep public away from danger area, NOTIFY POLICE AND FIRE BRIGADE IMMEDIATELY, According to paragraph 2.6.4.5 in Annex I to Regulation (EC) No 1272/2008, liquids with a flash point of more than 35 °C need not be classified in Category 3 if negative results have been obtained in the sustained combustibility test L.2, Part III, section 32 of the UN Manual of Tests and Criteria. This is however not valid under elevated conditions such as high temperature or pressure, and therefore such liquids are included in this entry.

Overland transport

Classification code (ADR) : C5

Limited quantities (ADR) : 1I

Excepted quantities (ADR) : E2

Packing instructions (ADR) : P001, IBC02

Mixed packing provisions (ADR) : MP15

Portable tank and bulk container instructions (ADR) : T7

Portable tank and bulk container special provisions (ADR) : TP2

Tank code (ADR) : L4BN

Vehicle for tank carriage : AT

Transport category (ADR) : 2

Hazard identification number (Kemler No.) : 80

Biogel

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Orange plates : 

Tunnel restriction code (ADR) : E
EAC code : 2R

Transport by sea

Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T7
Tank special provisions (IMDG) : TP2
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-B
Stowage category (IMDG) : A
Segregation (IMDG) : SGG18, SG35
Properties and observations (IMDG) : Colourless liquid. Colourless liquid. Reacts with ammonium salts, evolving ammonia gas. Causes burns to skin, eyes and mucous membranes. Reacts violently with acids.

Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y840
PCA limited quantity max net quantity (IATA) : 0.5L
PCA packing instructions (IATA) : 851
PCA max net quantity (IATA) : 1L
CAO packing instructions (IATA) : 855
CAO max net quantity (IATA) : 30L
Special provisions (IATA) : A3, A803
ERG code (IATA) : 8L

Inland waterway transport

Classification code (ADN) : C5
Limited quantities (ADN) : 1 L
Excepted quantities (ADN) : E2
Equipment required (ADN) : PP, EP
Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : C5
Limited quantities (RID) : 1L
Excepted quantities (RID) : E2
Packing instructions (RID) : P001, IBC02
Mixed packing provisions (RID) : MP15
Portable tank and bulk container instructions (RID) : T7
Portable tank and bulk container special provisions (RID) : TP2
Tank codes for RID tanks (RID) : L4BN
Special provisions for RID tanks (RID) : TU42
Transport category (RID) : 2
Colis express (express parcels) (RID) : CE6
Hazard identification number (RID) : 80

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
Contains no substance on the REACH candidate list

Biogel

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Other information, restriction and prohibition regulations

: Ensure all national/local regulations are observed. PIC Regulation EU (649/2012) - Export and Import of hazardous chemicals. {0} is subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

California Cleaning Product Right to Know Act of 2017 (SB 258)			
Component	CAS-No.	Function	List(s)
Water	7732-18-5	Diluent	Not Applicable
Butoxydiglycol	112-34-5	Solvent	Not Applicable
Emulsifier	Withheld	Cleaning Agent	Not Applicable
Sodium Hydroxide	1310-73-2	Cleaning Agent	Not Applicable
Amines, C12-14 Alkyldimethyl, N-oxides	308062-28-4	Cleaning Agent	Not Applicable
Alcohol	64-17-5	Solvent	List 9: IARC Carcinogens
Trisodium Dicarboxymethylalaninate	164462-16-2	Cleaning Agent	Not Applicable
Color mixture	Not available	Colorant	Not Applicable

15.1.2. National regulations

Germany

Regulatory reference

: WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Storage class (LGK, TRGS 510)

: LGK 8B - Non-combustible corrosive substances

Employment restrictions

: Observe restrictions according Act on the Protection of Working Mothers (MuSchG)
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Hazardous Incident Ordinance (12. BImSchV)

: Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen

: Ethanol is listed

SZW-lijst van mutagene stoffen

: None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding

: Ethanol is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid

: Ethanol is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling

: Ethanol is listed

Denmark

Class for fire hazard

: Class II-1

Store unit

: 5 liter

Classification remarks

: R10 <H314;H412>; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations

: Young people below the age of 18 years are not allowed to use the product

Norway

Declaration number

: 618312

15.2. Chemical safety assessment

No additional information available

Biogel

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

SECTION 16: Other information

Other information : **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Met. Corr. 1	Corrosive to metals, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS_U

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.