

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : FLEXO
 Product code : N41
 Type of product : Vehicle cleaning/vehicle care product
 Product group : Coating

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
 Use of the substance/mixture : See product bulletin for detailed information

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

CID LINES NV
 Waterpoortstraat, 2
 B-8900 Ieper - Belgique
 T + 32 57 21 78 77 - F +32 57 21 78 79
sds@cidlines.com - <http://www.cidlines.com>

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Australia	Poisons Information Centre		13 11 26	
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn B -1120 Brussels	+32 70 245 245	
Canada	CANUTEC Country Organization/Company Address Emergency number Comment		(613) 996-6666	
Finland	Poison Information Centre	P.O.B 790 (Tukholmankatu 17) HUS SF - 00029 Helsinki	+358 9 471 977	
Iceland	Eitrunarmiðstöð Landspítali	Fossvogi 108 Reykjavik	+354 543 22 22	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital MSD Msida	112	
Netherlands	Nationaal Vergiftigingen Informatie Centrum Uitsluitend bestemd om artsen te informeren bij accidentele vergiftigingen	Huispostnummer B.00.118, PO Box 85500 3508 GA Utrecht	+31 30 274 88 88	
New Zealand	The National Poisons Centre	University of Otago, 2nd Floor, Adams Building, 18 Frederick Street, 9016 Dunedin	0800 764 766 0800 POISON	
Switzerland	Centre Suisse d'Information Toxicologique Swiss Toxicological Information Centre, Schweizerisches Toxicologisches Informationszentrum STIZ	Freiestrasse 16 Postfach CH-8032 Zurich	+41 44 251 51 51 (International) 145 (National)	
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

FLEXO

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

USA	American Association of Poison Control Centers		1-800-222-1222	
-----	--	--	----------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Labelling according to OSHA 29 CFR 1910.1200

Flam. Liq. 3	H226
Acute Tox. 4 (Oral)	H302
Skin Irrit. 2	H315
Eye Dam. 1	H318
Asp. Tox. 1	H304

Full text of hazard classes and H-statements : see section 16


Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to OSHA 29 CFR 1910.1200

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazardous ingredients

: Distillates (petroleum), hydrotreated light; Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with; Naphta heavy

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.
H302 - Harmful if swallowed.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H318 - Causes serious eye damage.

Precautionary statements (CLP)

: P102 - Keep out of reach of children.
P210 - Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P260 - Do not breathe vapours, mist, spray.
P262 - Do not get in eyes, on skin, or on clothing.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P331 - Do NOT induce vomiting.
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTER or doctor/physician.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Naphta heavy	(CAS-No.) 64742-48-9 (EC-No.) 265-150-3 (EC Index-No.) 649-327-00-6	55 – 70	Carc. 1B, H350 Muta. 1B, H340 Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light	(CAS-No.) 64742-47-8 (EC-No.) 265-149-8 (EC Index-No.) 649-422-00-2 (REACH-no) 01-2119484819-18	3 – 12	Asp. Tox. 1, H304

FLEXO

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with	(CAS-No.) 475645-84-2 (EC-No.) 640-361-7	3 – 12	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412
ambient temperature curable refractory resin C	(CAS-No.) Confidential (REACH-no) 01-2119511367-43	3 – 12	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Seek medical attention immediately.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Seek medical advice (show the label where possible).
First-aid measures after eye contact	: Rinse immediately with plenty of water. Seek medical attention immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting because of corrosive effects. Take to hospital.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation of vapour can cause breathing difficulties. Cough. Sore throat.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Redness, pain. Blurred vision. Tears.
Symptoms/effects after ingestion	: Burning sensation. Cough. Cramps. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable Liquids.
Explosion hazard	: Not expected to be a fire/explosion hazard under normal conditions of use.
Reactivity in case of fire	: At high temperature may liberate dangerous gases.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire	: Wear fire/flare resistant/retardant clothing. Eliminate all ignition sources if safe to do so.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Exercise caution when fighting any chemical fire. Do not enter fire area without proper protective equipment, including respiratory protection. Wear fire/flare resistant/retardant clothing. Heat resistant gloves.
Other information	: On exposure to high temperature, may decompose, releasing toxic gases.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection. Stop leak if safe to do so. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Stop leak without risks if possible. Collect spillage. Use suitable disposal containers.
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it.

6.4. Reference to other sections

No additional information available

FLEXO

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: When handling product, avoid contact with skin and eyes. Wear personal protective equipment. Do not breathe vapour/aerosol. Provide good ventilation in process area to prevent formation of vapour.

Hygiene measures

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep only in the original container in a cool well ventilated place. Do not store in corrodable metal. Keep container closed when not in use. Protect from freezing.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Personal protective equipment:

Gloves. Protective goggles. protective clothing.

Hand protection:

Wear suitable gloves resistant to chemical penetration

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0.5	2 (< 1.5)	EN ISO 374

Eye protection:

Wear security glasses which protect from splashes

Type	Field of application	Characteristics	Standard
Safety glasses, Safety goggles, Face shield	Droplet	Clear, Plastic.	EN 166

Skin and body protection:

Wear suitable protective clothing

Type	Standard
	EN14605:2005+A1:2009

Respiratory protection:

Appropriate dust or mist respirator should be used if airborne particles are generated when handling this material

Device	Filter type	Condition	Standard
Half-mask	Filter type A/P2	Long term exposure, Vapour protection	EN 132, EN 140

Personal protective equipment symbol(s):



Other information:

When using do not eat, drink or smoke. Provide local exhaust or general room ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

: Liquid

Colour

: Colourless.

Odour

: No data available

Odour threshold

: No data available

pH

: No data available

FLEXO

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 65 °C
Flash point	: 50 °C
Auto-ignition temperature	: 262 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 0.075 Pa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.95 kg/l
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 0.6 vol %
Upper explosive limit (UEL)	: 5.4 vol %

9.2. Other information

VOC content	: 539.15 g/l
-------------	--------------

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal conditions.

10.2. Chemical stability

The product is stable at normal handling and storage conditions.

10.3. Possibility of hazardous reactions

None under normal conditions.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

FLEXO

LD50 oral rat	1000 mg/kg
---------------	------------

Naphta heavy (64742-48-9)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	--

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.

FLEXO

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Carcinogenicity	: Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262- P301 + P310-P331 (Table 3.1) or the S-phrases (2-)23-24-62 (Table 3.2) shall apply. This note applies only to certain complex oil-derived substances in Part 3.
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other adverse effects : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Dispose in a safe manner in accordance with local/national regulations.
Waste treatment methods	: Dispose of this material and its container at hazardous or special waste collection point. Hazardous waste due to toxicity. Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: When totally empty, containers are recyclable like any other packing. Dispose in a safe manner in accordance with local/national regulations. Avoid release to the environment.
European List of Waste (LoW) code	: 07 06 01* - aqueous washing liquids and mother liquors
Switzerland - Waste code (VeVA)	: 07 06 01 - [ak] Aqueous washing liquids and aqueous mother liquors

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number

UN-No. (ADR)	: UN 1993
UN-No. (IMDG)	: UN 1993
UN-No. (IATA)	: UN 1993
UN-No. (ADN)	: UN 1993
UN-No. (RID)	: UN 1993

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: FLAMMABLE LIQUID, N.O.S. (ambient temperature curable refractory resin C ; Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with)
Proper Shipping Name (IMDG)	: FLAMMABLE LIQUID, N.O.S. (ambient temperature curable refractory resin C ; Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with)
Proper Shipping Name (IATA)	: Flammable liquid, n.o.s. (ambient temperature curable refractory resin C ; Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with)
Proper Shipping Name (ADN)	: FLAMMABLE LIQUID, N.O.S. (ambient temperature curable refractory resin C ; Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with)
Proper Shipping Name (RID)	: FLAMMABLE LIQUID, N.O.S. (ambient temperature curable refractory resin C ; Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with)

FLE XO

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

Transport document description (ADR)	: UN 1993 FLAMMABLE LIQUID, N.O.S. (ambient temperature curable refractory resin C ; Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with), 3, III, (D/E)
Transport document description (IMDG)	: UN 1993 FLAMMABLE LIQUID, N.O.S. (ambient temperature curable refractory resin C ; Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with), 3, III
Transport document description (IATA)	: UN 1993 Flammable liquid, n.o.s. (ambient temperature curable refractory resin C ; Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with), 3, III
Transport document description (ADN)	: UN 1993 FLAMMABLE LIQUID, N.O.S. (ambient temperature curable refractory resin C ; Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with), 3, III
Transport document description (RID)	: UN 1993 FLAMMABLE LIQUID, N.O.S. (ambient temperature curable refractory resin C ; Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with), 3, III

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3



ADN

Transport hazard class(es) (ADN) : 3
Danger labels (ADN) : 3



RID

Transport hazard class(es) (RID) : 3
Danger labels (RID) : 3



FLEXO

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

14.4. Packing group

Packing group (ADR)	: III
Packing group (IMDG)	: III
Packing group (IATA)	: III
Packing group (ADN)	: III
Packing group (RID)	: III


14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

14.6. Special precautions for user

Special transport precautions	: Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency, No naked flames, sparks, and do not smoke, Keep public away from danger area, NOTIFY POLICE AND FIRE BRIGADE IMMEDIATELY
-------------------------------	--

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 274, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBF
Vehicle for tank carriage	: FL
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Operation (ADR)	: S2
Hazard identification number (Kemler No.)	: 30
Orange plates	: 

Tunnel restriction code (ADR)	: D/E
EAC code	: •3YE

Transport by sea

Special provisions (IMDG)	: 223, 274, 955
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-E
EmS-No. (Spillage)	: S-E
Stowage category (IMDG)	: A

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y344
PCA limited quantity max net quantity (IATA)	: 10L
PCA packing instructions (IATA)	: 355
PCA max net quantity (IATA)	: 60L
CAO packing instructions (IATA)	: 366
CAO max net quantity (IATA)	: 220L
Special provisions (IATA)	: A3

FLEXO

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

ERG code (IATA) : 3L

Inland waterway transport

Classification code (ADN) : F1

Special provisions (ADN) : 274, 601

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01

Number of blue cones/lights (ADN) : 0

Rail transport

Classification code (RID) : F1

Special provisions (RID) : 274, 601

Limited quantities (RID) : 5L

Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Mixed packing provisions (RID) : MP19

Portable tank and bulk container instructions (RID) : T4

Portable tank and bulk container special provisions (RID) : TP1, TP29

Tank codes for RID tanks (RID) : LGBF

Transport category (RID) : 3

Special provisions for carriage – Packages (RID) : W12

Colis express (express parcels) (RID) : CE4

Hazard identification number (RID) : 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 539.15 g/l

Other information, restriction and prohibition regulations : Ensure all national/local regulations are observed. PIC Regulation EU (649/2012) - Export and Import of hazardous chemicals. {0} is subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

California Cleaning Product Right to Know Act of 2017 (SB 258)

Component	CAS-No.	Function	List(s)
C10-12 Alkane	64742-48-9	Solvent	Not applicable
Cyclosilazanes, di-Me, Me hydrogen, polymers with di-Me, Me hydrogen silazanes, reaction products with 3-(triethoxysilyl)-1-propanan	475645-84-2	Cleaning agent	Not applicable
C13-14 Alkane	64742-47-8	Solvent	Not applicable

15.1.2. National regulations

15.2. Chemical safety assessment

No additional information available

FLEXO

Safety Data Sheet

According to OSHA 29 CFR 1910.1200

SECTION 16: Other information

Other information : **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1B	Carcinogenicity, Category 1B
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 1B	Germ cell mutagenicity, Category 1B
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H340	May cause genetic defects.
H350	May cause cancer.
H412	Harmful to aquatic life with long lasting effects.

SDS_U

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.